

# MSR Gold™ 700 SA/2 DE LCT

## Product family description

MSR Gold™ SA Double Ended – for extended performanceTo optimize the total lifetime of the double ended MSR Gold™ SA Double Ended lamps, the caps are plated with gold. This provides superior heat protection and thereby minimizes premature failure of the lamp and lamp holder, as well as ensuring extended consistent performance. In addition, the highly innovative P3 technology, developed by Philips, allows the lamp to be used at higher temperatures, which further extends service life and consistency of high-quality light output.

### **Product Features**

- Philips Pinch Protection
- MSR filling
- Gold plated lamp caps

## **Product Benefits**

- Enables use at higher temperatures in any burning position. Longer lifetime, fewer early failures, consistent performance over time
- Pure, white light; color point close to black body line.
  Consistent color impression over MSR Range
- Reduces early lamp or lamp holder failures

Product data						
Order code	908589 00					
Full product name	MSR Gold™ 700 SA/2 DE ICT					
Packing type	I Carton					
Pieces per pack	I					
Net weight per piece	0.034 KG					
Successor order code						
System Description	SA/2 DE					
Cap-Base	SFC10-4					
Cap-Base Information	SFC10-4					
Execution						
Operating Position	any					
Main Application	Studio/Disco					



	Dundana dan						
Product data							
Additional Information	•						
Packing Type	ICT [I Carton]						
Packing Configuration	16						
Life to 50% failures EM	750 hr						
Lamp Wattage	700W						
Technical Type	700						
Lamp Wattage Technical	700 W						
Lamp Current	11.5 A						
Color Code							
Color Rendering Index	75 Ra8						
Color Temperature	7500 K						
Luminous Flux Lamp EM	56000 Lm						
Luminous Efficacy Lamp EM	80 Lm/W						





 $\mathsf{MSR}\;\mathsf{Gold^{\mathsf{TM}}}\;\mathsf{SA(/2)}\;\mathsf{DE}$ 

MSR Gold 1200W/700W/900W/1500W/400W SA/2 DE/SA/DE



MSR Gold™ 1200 SA/DE






Cap-Base SFC10-4


**Operating Position any** 








MSR Gold 700W SA/2 DE



MSR Gold 700W SA/2 DE



MSR Gold™ SA/DE

#### MSR Gold 1200W/1500W/400W/575W/700W SA/2 DE/SA/DE

	A	A	A	A	A	A
Full produc t name	Min	Min	Nom	Nom	Max	Max
MSR Gold ™ 700	114.4	114.4	114.8	114.8	115.2	115.2



	A	A	A	A	A	A
Full produc t name SA/2 DE ICT	Min	Min	Nom	Nom	Max	Max
	С	С	D	D	D1	D1
Full produc t name	Max	Max	Max	Max	Nom	Nom
MSR Gold ™ 700 SA/2 DE ICT	136	136	19	19	-	-
	F	F	F	F	F	F
Full produc t name	Min	Min	Nom	Nom	Max	Max
MSR Gold ™ 700 SA/2 DE ICT	-	-	-	-	-	-
	L	L	L	L	L	L
Full produc t name	Min	Min	Nom	Nom	Max	Max
MSR Gold ™ 700 SA/2 DE ICT	-	-	-	-	-	-
			0		O	
Full pro	Full product name		Nom	m Nom		
	d™ 700 SA/ E ICT		4.0		4.0	



# $\hbox{@2009 Koninklijke Philips Electronics N.V.}\\$

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liablity will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Document order number : 0000 000 00000